

Featuring the **acker R.A.D.**

Log on to www.youtube.com/ackerdrill to see the R.A.D. travel through a standard sized doorway.

Features:

- **Minimum Width 33-1/2"**
- Drill Clearance Under 8'
- 3,000 ft. lb. Hydraulic Drill Head
- 10,900 lb. Thrust/Pullback
- Deutz Diesel Powered
(Propane, Electric & Pneumatic Also Available)
- Mast Extensions Up to 11 ft. Stroke
- Expandable Tracks
- Truck, Track, Trailer or Skid Mounted



Electric Powered



R.A.D. = Restricted Access Drill

R.A.D. STANDARD FEATURES:

A.	Power Unit - 58 HP @ 2,300 RPM diesel engine with 12-volt electric start engine. Optional Electric TEFC 3-phase 460VAC induction motor @ 1,800 RPM. Other power options available.
B.	Feed Mechanism - The main feed consists of a chain drive mechanism with options of a 3 ft., 7 ft. or 11 ft. feed, through a planetary hydraulic drive unit. Thrust and pull @ 10,900 lbs.
C.	Drill Drive - Taken from prime mover through a variable volume over center piston pump and tandem fixed volume pump.
D.	Drill Head - 3-5/8" open spindle. 1st gear (0-120 RPM @ 3,028 ft./lbs. torque) 2nd gear (0-252 RPM @ 1,452 ft./lbs. torque) 3rd gear (0-456 RPM @ 788 ft./lbs. torque) 4th gear (0-750 RPM @ 458 ft./lbs. torque) Drill head has a lateral slide feature. "Optional" hinge-type available.
E.	Mast - Welded rectangular structural steel tube construction that supports and guides the rotation of feed components. Positioned with one (1) hydraulic cylinder and rigidly held in the vertical position for drilling and is lowered to the travel position for moving from hole to hole. Mast mounting allows for angle as well as 90 degree vertical drilling. Mast is capable of drilling under 8 ft. ceilings with low clearance sheaves.
F.	Main Drum Hoist - 4,500 lbs. Planetary type with 75 ft. of 5/16" cable (hydraulically powered).
G.	Track Mounting - The entire drill is mounted on a structural steel frame and is self-propelled by 9" rubber crawler tracks with independent reversible hydraulic motor drive. Tracks are 33-1/2" wide retracted and 39-1/2" wide extended. Includes provision for (4) lifting points for crane lift.
H.	Hydraulic Oil Cooler
I.	Hydraulic Leveling Jacks - (4) "Swing Away"

R.A.D. OPTIONAL FEATURES:

1.	Cathead Hoist - Hydraulically powered cargo type hoist.
2.	Quick Disconnect Adapter - U-Joint type for augers, 1-5/8" hex.
3.	Auger Guide - Specify size required.
4.	Water Pump - Hydraulically driven with infinitely variable speed controls from the operator's station. Moyno type 3L4, 3L6 or equal.
5.	Front Winch - Hydraulically driven, front-mounted with 12,000 lbs. capacity. Capable of operating in conjunction with tracks from remote control.
6.	Ackermatic Hydraulic Chuck - 4" chuck handles rod and casing up to 3-1/2" O.D.
7.	Probe Hammer
8.	Full Function Remote Radio Control for Tramming/Winch Operations with Emergency Shutdown

Contact factory for additional details. A complete line of optional accessories are available.



P.O. Box 830, Scranton, PA 18501

Toll Free: 800.752.2537 Fax: 570.586.2659

E-Mail: sales@ackerdrill.com Website: www.ackerdrill.com

